



# 480 mm radius

ROUNDED CONTOUR-PROFILE

510

#### PREVENTION

•Use water and neutral soap to clean the windshield. • Check the tightening of the fasteners peridiocally. •Park the scooter facing the sun, avoiding the sunreflection effect that may damage some parts. • Park if possible on even surfaces.

#### Thanks for your attention.

| ID. | DESCRIPTION                        | QTY. |
|-----|------------------------------------|------|
| 1   | Clear windshield                   | 1    |
| 2   | Metal support Ø10xØ10              | 2    |
| 3   | Plastic support                    | 2    |
| 4   | Plastic washer                     | 4    |
| 5   | 5,5x14 screw to tight into plastic | 2    |
| 6   | Support with drill through         | 2    |
| 7   | Screw with drill through           | 2    |
| 8   | Special washer                     | 2    |
| 9   | Ø10x200 bar                        | 2    |
| 10  | M8 nut cover                       | 4    |
| 11  | M8x30 screw DIN 931                | 2    |
| 12  | 5,5x12 screw to tight into plastic | 2    |
| 13  | Ø8 washer DIN 9021                 | 2    |
| 14  | Ø14xØ8x6 arrowhead                 | 2    |
| 15  | M8 DIN 6923 nut                    | 2    |
| 16  | Screw cap                          | 4    |
| 17  | DIN985 M8 lock nut                 | 2    |
| 18  | Ø10 nylon washer                   | 4    |
| 19  | M10 nut cover                      | 2    |

### WINDSHIELD ADAPTABLE TO SYM SYMPHONY SR

## Mod.: TS Ref.: 5856W



