

Porting To the second s

PREVENTION

- •Use water and neutral soap to clean the windshield.
- Check the tightening of the fasteners peridiocally.
- Park the scooter facing the sun, avoiding the sunreflection effect that may damage some parts.
- Park if possible on even surfaces.

Thanks for your attention.

		OTV
ID.	DESCRIPTION	QTY.
1	Windshield	1
2	Exterior cap	2
3	Ball bearing exterior support	2
4	Ball bearing interior support	2
5	M5x20 DIN912 allen screw	4
6	M5 DIN982 lock nut	4
7	M5x13 phillips screw	4
8	Straight rod Ø9x180	2
9	Final bar cap	2
10	M8x40 DIN912 screw	2
11	Rod guide support	2
12	Coupling angle	2
13	Ø8 Ø10 angle Ref.:582	2
14	M8 nut cover	2
15	Ø16xØ10'5x20 spacer	2
16	M8 DIN6923 nut	2
17	M8 DIN912 screw cap	2
18	Below drill cover	1
19	M10 DIN934 nut left thread (right side)	1
20	M10x35 screw left thread (right side)	2
21	M10 nut cover	2
22	Ø10xØ10 rearview support	2
23	M10 flat washer	2
24	M10 nut (left side)	1
25	M10x35 screw (left side)	1

WINDSHIELD ADAPTABLE TO

YAMAHA D'ELIGHT

Mod.: TRAFIC Ref.: **6882**

Mod.: URBAN Ref.: **8480**

