




### PREVENTION

- Use water and neutral soap to clean the windshield.
- Check the tightening of the fasteners periodically.
- Park the scooter facing the sun, avoiding the sun-reflection effect that may damage some parts.
- Park if possible on even surfaces.

Thanks for your attention.



It would be convenient to re-tight the windshield screws, specially the ones that are fixed to the motorcycle, whenever you maintain the vehicle.  
Thanks for your attention.

ID.	DESCRIPTION	QTY.
1	Windshield	1
2	Exterior cap	2
3	Ball bearing exterior support	2
4	Ball bearing interior support	2
5	M5x20 DIN912 allen inox screw	4
6	M5 DIN982 lock inox nut	4
7	M5x13 phillips screw	4
8	Rod with ball bearing to 90° Ø9x150	2
9	Final bar cap	2
10	M8x40 D912 screw	2
11	Rod guide support	2
12	Coupling angle	2
13	Angle Ref.:581	2
14	M8 nut cover	2
15	M8 DIN6923 nut	2
16	M8 DIN912 screw cap	2
17	Ø14xØ8,5x20 spacer	2
18	Below drill cover	2
19	Ø16xØ10x12 spacer	2

WINDSHIELD ADAPTABLE TO  
**PEUGEOT DJANGO 125I**

Mod.: TRAFIC  
Ref.: 9216

Mod.: URBAN  
Ref.: 9217

