



FITTING INSTRUCTIONS FOR R&G TANK/TAIL SLIDERS



The above picture are representative only

In this kit you will have

- A pair of tank/tail sliders.
- A tube of silicone sealant.

SURFACE PREPARATION

- Place the tank/tail slider in position so you know the area you will have to clean.
- Thoroughly clean the surface ensuring it is free of road-grime etc. (an alcohol wipe will ensure cleanliness).
- Thoroughly clean the inside face of tank/tail sliders (again an alcohol wipe will ensure cleanliness).
- Coat the inside of the tank/tail slider with the silicone sealant (do not use too much as this becomes messy and difficult to remove).
- Position the tank/tail slider and apply pressure to remove air and allow bonding. Remove excess from edges immediately as the longer this is left the more difficult it is to remove. We recommend securing the slider with masking tape (or similar) to the bike fairing/tank during the curing process to ensure proper adhesion.
- Please leave for a minimum of twenty-four hours before riding the motorcycle.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.