



**FITTING INSTRUCTIONS FOR EH0053BK/ EXHAUST HANGER**  
**APRILIA RSV4 WITH AKRAPOVIC SLIP ON CAN ONLY**



**Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike**

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

- Remove OEM rear foot pegs/exhaust hanger.
- Place the two longer M8 button head bolts from kit through the two top holes in the R&G hanger.
- Place the two spacers over the exposed end of both bolts.
- Offer up to bike as shown above and engage threads (do not tighten yet).
- Place the shorter M8 button head bolt from kit and position as arrowed through exhaust mount as shown.
- Place the M8 nyloc nut onto exposed end of bolt and tighten all bolts evenly.
- Please ensure when the motorcycle is being used that no parts are in such a position that they may collide/damage other bike parts (this is particularly important if using after-market cans or exhaust systems).

***Please note that it is your responsibility to ensure that no part of the exhaust hanger or exhaust assembly fouls or comes into contact with other parts of the machine. Do not ride the motorcycle until this aspect has been verified and you have compressed the rear suspension (if appropriate to the design of the motorcycle) to test this thoroughly.***