



FITTING INSTRUCTIONS FOR CP0151BL FRONT CRASH PROTECTORS TRIUMPH SPEED TRIPLE '97 ONWARDS

PLEASE NOTE THAT THE WAY THAT THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF MOUNTING TO THE BIKE

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

Nearside (left side as you sit on the bike)

- Remove FRONT engine mount bolt (see the FRONT protector in the above picture for position)
- Take the shorter M12 hex head bolt, pass it through the washer AND ALSO the original washer from the bike
- Then pass it through the smaller of the two protectors
- Slide one of the aluminium spacers up behind the bobbin
- Offer the assembly up to the bike
- Push the bolt through the hole - place original engine nut on the back and tighten bolt until you feel some compression from inside the protector. Turn a little more so that you feel the compression increase slightly. Then apply a quarter turn. Do not overtighten as damage can occur to the bike. Do not exceed 40nm of torque.

Offside

- Remove FRONT engine mount bolt
- Take the longer M12 hex head bolt, pass it through the washer AND ALSO the original washer from the bike
- Then pass it through the protector with a neck
- Slide one of the aluminium spacers up behind the bobbin
- Offer the assembly up to the bike
- Push the bolt through the hole - place original engine nut on the back and tighten bolt until you feel some compression from inside the protector. Turn a little more so that you feel the compression increase slightly. Then apply a quarter turn. Do not overtighten as damage can occur to the bike. Do not exceed 40nm of torque.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order.
The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes.
Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products.
On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.
Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned.
These terms do not affect the Buyer's statutory rights.