

2019 RK CHAIN APPLICATIONS

CHAIN	NATURAL	GOLD	COLOR	SEAL	STREET	OFF-ROAD	MX	RACE	ATV	TENSILE** (lbs)	MAX HORSE POWER	Fatigue (lbs)	WEAR LIFE†	WEIGHT* (lbs)	MAX CHAIN WIDTH *** (mm)
ROAD RACE SPECIFIC															
415HRU	-	✓	-	U				250		4,800	60 HP	880	700	1.52	15.4
520UWR	-	✓	-	UW				1300		8,400	180 HP	1930	3100	3.44	18.8
DRAG RACE SPECIFIC															
530DR	✓	-	-	-				1500		10,400	250 HP	2630	100	4.96	24.7
530PRODR	✓	-	-	-				1500		11,880	350 HP	2470	440	NA	26.6
STRONGEST ON THE STREET															
520ZXW	-	✓	✓	XW	1200					9,450	200 HP	2181	3800	3.92	20.8
525ZXW	-	✓	✓	XW	1300					10,430	220 HP	2650	4100	4.56	23.4
530ZXW	-	✓	✓	XW	1400					11,200	220 HP	2650	4200	4.89	25.4
STRONG & DURABLE HIGH PERFORMANCE STREET & OFF ROAD															
520GXW	✓	✓	✓	XW	1200	750		1200		8,700	200 HP	2180	3750	3.70	20.8
525GXW	✓	✓	✓	XW	1300	800		1300		8,900	200 HP	2200	3900	4.13	22.9
530GXW	✓	✓	✓	XW	1400	900		1400		9,900	205 HP	2650	4050	4.65	24.5
LIGHT WEIGHT HIGH PERFORMANCE STREET & OFF ROAD															
428XSO	✓	✓	-	RX	400	350				6,070	60 HP	1530	2700	2.65	22.3
520XSO	✓	✓	✓	RX	750	750			750	8,300	80 HP	2180	3500	3.44	21.7
525XSO	✓	✓	-	RX	900	750				8,400	150 HP	2200	3700	4.13	22.9
530XSOZ1	✓	✓	✓	RX	1000	750				9,000	150 HP	2430	3900	4.36	24.5
ECONOMICAL SEALED STREET															
520SO	✓	-	-	O	400	400			400	6,900	60 HP	1710	2400	3.39	21.7
OFF ROAD / ATV RACE SPECIFIC															
520EXW	✓	✓	-	XW		750		750	750	7,700	70 HP	1930	3300	3.70	22.0
OFF ROAD / ENDURO RACE SPECIFIC															
520MXU	-	✓	-	UW		500	500	500		8,000	70 HP	1930	3200	3.04	19.1
PRO MX / SX RACE SPECIFIC - MXZ4 Series comes with Hard chrome Coating pin with Extended wear life															
420MXZ4	-	✓	-	-		150	150	150		5,400	40 HP	970	450	1.83	17.8
428MXZ4	-	✓	-	-		150	150	150		6,100	40 HP	1460	450	2.21	20.1
520MXZ4	✓	✓	✓	-		500	500	500		8,000	70 HP	2180	450	3.02	18.8
WEEKEND WARRIOR MX / SX															
420MXZ	✓	✓	-	-		150	150	150		4,980	30 HP	880	200	1.73	17.1
428MXZ	✓	✓	-	-		150	150	150		5,800	30 HP	1215	200	2.09	18.9
MAX SERIES - Maximum performance, Maximum Value															
520MAXO	✓	✓	-	O	750	650			650	8,500	80 HP	1930	2400	3.51	21.4
525MAXO	✓	✓	-	O	900	750				9,300	150 HP	2180	2400	4.38	23.8
530MAXO	✓	✓	-	O	1000	750				9,700	150 HP	2650	2400	4.77	25.7
520MAXX	✓	✓	✓	RX	1000	750			750	9,000	120 HP	2180	3600	4.02	22.0
525MAXX	✓	✓	✓	RX	1100	900				9,300	175 HP	2180	3700	4.38	23.8
530MAXX	✓	✓	✓	RX	1100	900				9,700	180 HP	2650	3700	4.77	25.7
520MAXZ	✓	✓	✓	RX	1200					9,400	200 HP	2425	3600	4.18	21.2
525MAXZ	✓	✓	✓	RX	1300					10,420	220 HP	2425	4000	4.68	23.4
530MAXZ	✓	✓	✓	RX	1400					11,200	220 HP	2650	4000	4.99	25.4
HEAVY DUTY															
M415H	✓	-	-	-	125	80				4,100	50 HP	970	200	1.59	14.6
M420H	✓	-	-	-	125	90				4,100	15 HP	970	200	1.79	16.9
M428H	✓	-	-	-	200	125				5,400	15 HP	1215	200	2.22	20.3
M520H	✓	-	-	-	400	250				7,700	30 HP	1930	200	3.51	19.7
M525H	✓	-	-	-	500					7,700	40 HP	1930	200	3.73	21.3
M530H	✓	-	-	-	500					7,700	40 HP	1930	200	4.17	22.9
530KS	✓	-	-	-	400					7,100	60 HP	1930	200	3.75	21.9
STANDARD															
M420	✓	-	-	-	125	90				4,000	10 HP	970	100	1.65	16.2
M428	✓	-	-	-	150	125				4,500	12 HP	970	100	1.85	18.9
M520	✓	-	-	-	250	250				6,800	20 HP	1460	100	3.28	18.5
M525	✓	-	-	-	400					6,800	30 HP	1460	100	3.51	19.9
M530	✓	-	-	-	400					6,800	30 HP	1460	100	3.73	21.7

RK recommends using a chain model with the maximum amount of displacement and horsepower ratings based on motorcycle's original equipped chain size.
 † = WEAR LIFE figure is a comparison between RK Chain models. Baseline is RK's non-sealed standard chains at 100. WEAR LIFE should not be used to compare other brand of chains.
 * = LBS/100 Links
 ** = LBS/FT
 *** = Need a wider amount of space than the maximum chain width in order to install the chain.