



	PIN LENGTH MM	PLATE		SEAL	2016 TENSILE LBS/FT‡	2016 FATIGUE LBS/FT‡	CLIP or RIVET	WEIGHT LBS/100 LINKS	MAX cc STREET / OFF-ROAD
		THICKNESS							
		INNER MM	OUTER MM						
MAX O SERIES									
520MAXO	19.9	2.0	2.0	O	8,500	1,930	CLIP/RIVET	3.51	750 / 650
525MAXO	22.6	2.4	2.2	O	9,300	2,180	RIVET	4.38	900 / 750
530MAXO	24.9	2.4	2.4	O	9,700	2,650	RIVET	4.77	1000 / 750
MAX X SERIES									
520MAXX	20.8	2.2	2.2	RX	9,000	2,180	CLIP/RIVET	4.02	1000 / 750
525MAXX	22.6	2.4	2.2	RX	9,300	2,180	RIVET	4.38	1100 / 900
530MAXX	24.9	2.4	2.4	RX	9,700	2,650	RIVET	4.77	1100 / 900
MAX Z SERIES									
520MAXZ	21.2	2.2	2.4	RX	9,400	2,425	RIVET	4.18	1200 / NA
525MAXZ	23.4	2.4	2.6	RX	10,420	2,425	RIVET	4.68	1300 / NA
530MAXZ	25.8	2.6	2.6	RX	11,200	2,650	RIVET	4.99	1400 / NA
RK JAPAN HEAVY DUTY									
420MXZ4	16.6	1.8	1.8	NONE	5,400	970	CLIP	1.90	NA / 150
428MXZ4	18.7	2.0	2.0	NONE	6,100	1,500	CLIP	2.25	NA / 150
520MXZ4	17.7	1.8	2.0	NONE	8,000	2,200	CLIP	3.15	NA / 500
530KS	20.8	2.0	2.0	NONE	7,100	1,900	CLIP	3.90	400 / NA
530DR <i>Drag Racing</i>	23.3	2.6	2.4	NONE	10,400	2,600	CLIP	5.16	1500 Drag
RK JAPAN STANDARD O-RING									
520SO	19.9	2.0	2.0	O	6,900	1,700	CLIP/RIVET	3.46	400 / NA
525SO	22.9	2.4	2.3	O	8,400	2,200	CLIP/RIVET	4.21	800 / NA
530SO	24.9	2.4	2.3	O	9,000	2,400	CLIP/RIVET	4.45	900 / NA
RK JAPAN PERFORMANCE RX-RING									
520XSO	19.9	2.0	2.0	RX	8,300	2,200	CLIP/RIVET	3.51	750 / 750
525XSO	22.9	2.4	2.3	RX	8,400	2,200	CLIP/RIVET	4.21	900 / 750
530XSOZ1	24.9	2.4	2.3	RX	9,000	2,400	CLIP/RIVET	4.45	1000 / 750
RK JAPAN PERFORMANCE UW-RING									
GB415HRU <i>NSF250R</i>	14.0	1.5	1.5	UW	4,800	880	CLIP	1.57	250 / NA
GB520MXU <i>SX/MX</i>	18.0	1.8	2.0	UW	8,000	1,900	CLIP	3.21	NA / 500
RK JAPAN PREMIUM XW-RING									
520EXW	20.8	2.2	2.2	XW	7,700	1,900	CLIP	3.77	NA / 750
520GXW	20.8	2.2	2.2	XW	8,700	2,200	RIVET	3.77	1200 / 750
525GXW	22.9	2.4	2.3	XW	8,900	2,200	RIVET	4.21	1300 / 800
530GXW	24.9	2.4	2.4	XW	9,900	2,700	RIVET	4.65	1400 / 900
STANDARD RK-MALAYSIA									
M420	14.8	1.5	1.5	NONE	4,100	880	CLIP	1.65	110 / 90
M428	16.9	1.5	1.5	NONE	4,300	880	CLIP	1.85	135 / 125
M520	17.3	2.0	2.0	NONE	6,600	1,300	CLIP	3.28	250 / NA
M525	18.7	2.0	2.0	NONE	6,600	1,300	CLIP	3.51	250 / NA
M530	20.5	2.0	2.0	NONE	6,600	1,300	CLIP	3.73	250 / NA
HEAVY DUTY RK-MALAYSIA									
M415H <i>mini bike chain</i>	13.1	1.5	1.5	NONE	4,100	880	CLIP	1.59	110 / 80
M428H	18.8	2.0	2.0	NONE	5,400	1,100	CLIP	2.22	200 / 125
M520H	18.8	2.3	2.3	NONE	7,700	1,760	CLIP	3.51	250 / NA
M525H	20.4	2.3	2.3	NONE	7,700	1,760	CLIP	3.73	250 / NA
M530H	22.0	2.3	2.3	NONE	7,700	1,760	CLIP	4.17	250 / NA