

Ⓜ Advice for correct fitting of the kit: Do not fully tighten the screws until it is ensured that the KIT is correctly attached and aligned.



Ⓜ Open the seat (A). Dismantle the embellishment upper cap from the folding seat (B), which is discarded, and the lower cap (C).



Ⓜ Dismantle and discard the screws (D), in zone (F).



Ⓜ Assemble the KIT TOP upper support (1) in zone (F), with spacers (2), screws (3) and washers (4). And in zone (G), with the spacer (5), washer (4), screw (6) and nut (7). Assemble the bottom cap (C).

4.



(GB) Place the lower KIT TOP support (8) to the folding seat with washers (9) and screws (10), join it to the upper KIT TOP support (1) with screws (11), washers (12) and nuts (13).

5.



(GB) Close the seat (A).

PARTS.

Pos.	Ref.		Cant.	
1	260869		1	Upper KIT TOP Support
2	260747		2	Ø20 Ø9 x 13 - Spacer
3	304053		2	M8 x 30 DIN 7380 - Screw
4	303020		3	Ø8 DIN 125 - Washer
5	260712		1	Ø20 Ø11 x 22 - Spacer
6	304032		1	M8 x 50 din 7991 - Screw
7	302024		1	Self-blocking Nut M8
8	260872		1	Lower KIT TOP Support
9	303017		2	Ø18XØ6 - Special washer
10	304012		2	M6X16 DIN 912 - Screw
11	304091		2	M6X20 DIN 7991 - Screw
12	303000		2	Ø6 DIN 125 - Washer
13	302021		2	Self-blocking Nut M6