



# **SHINKO**

**MOTORCYCLE TIRES**









# **TABLE OF CONTENTS**

VTWIN / CRUISER.....	4-17
SPORT / SPORT TOURING.....	18-29
DRAG / RACE / SPECIALTY .....	30-35
DUAL SPORT.....	36-41
SMALL BORE.....	42-47
OFFROAD .....	48-59
PROMOTIONAL .....	62-63
TIRE GUIDE.....	64-65









***VTWIN / CRUISER***









## SR999 LONG HAUL

The all new SR999 Long Haul Tire is designed for the cruiser rider looking for exceptional tread life and performance! Enjoy the cross country miles to your destination and the twisties once you get there! The Shinko SR999 is in it for the Long Haul!

- All new rubber compound formulated for high mileage and inspiring grip
- Functional tread grooves for superior traction in wet and dry conditions
- Reinforced carcass for a stable and planted feel
- Aramid belting provides ample load capacity while also providing stability

Size	Load/Speed Rating	TT/TL	WPS #
<b>FRONT</b>			
130/90B16	73H	TL	<b>87-4903</b>
130/80-17	65H	TL	<b>87-4900</b>
130/70B18	69H	TL	<b>87-4911</b>
100/90-19	61H	TL	<b>87-4904</b>
130/60B19	67H	TL	<b>87-4909</b>
80/90-21	54H	TL	<b>87-4914</b>
120/70B21	68V	TL	<b>87-4902</b>

Size	Load/Speed Rating	TT/TL	WPS #
<b>REAR</b>			
170/80B15	73H	TL	<b>87-4912</b>
130/90B16	73H	TL	<b>87-4905</b>
140/90B16	77H	TL	<b>87-4915</b>
150/80B16	77H	TL	<b>87-4906</b>
170/70B16	75H	TL	<b>87-4913</b>
180/65B16	81H	TL	<b>87-4907</b>
MU85B16	77H	TL	<b>87-4901</b>
160/70B17	79H	TL	<b>87-4908</b>
180/55B18	84H	TL	<b>87-4910</b>









## SR777 & SR777 H.D. BLACK WALL

Shinko SR777 & SR777 H.D tires are specifically designed for the rider looking for the ultimate performance cruiser tire! The SR777 compound is formulated for maximum grip and control to inspire confidence! Available in a multitude of sizes to fit many V-Twin and metric cruiser models.

- Rubber compound formulated to provide maximum grip and comfort
- Tread design includes functional siping and grooves for superior traction in wet and dry riding conditions
- Confidence inspiring traction you can feel when accelerating, braking and cornering
- H.D. (Heavy Duty) version with reinforced carcass providing a more stable and planted feel
- Aramid belted provides ample load capacity while also giving more stability
- Unleash the handling potential of your cruiser motorcycle
- Legendary SR 777 handling and performance available in a DOT Approved 30"
- SRT 777 HD 6.5"-20 with a true front tire profile and tread to ensure superior handling. Requires Paul Yaffe's 20" Big Wheel performance SRT Kit.

Size	Load/Speed Rating	TT/TL	WPS#	Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>				<b>REAR</b>			
130/90B16 HD	73H	TL	<b>87-4585</b>	150/90B15 HD	80H	TL	<b>87-4590</b>
150/80-16	71H	TL	<b>87-4604</b>	160/80-15	74H	TL	<b>87-4572</b>
120/90-17	64H	TL	<b>87-4560</b>	170/80B15 HD	83H	TL	<b>87-4592</b>
140/80-17	69H	TL	<b>87-4561</b>	180/70B15 HD	82H	TL	<b>87-4614</b>
130/80-17	65H	TL	<b>87-4566</b>	130/90B16 HD	73H	TL	<b>87-4594</b>
120/90-18	65H	TL	<b>87-4563</b>	MU85B16 HD	77H	TL	<b>87-4568</b>
130/70B18 HD	69H	TL	<b>87-4616</b>	140/90B16 HD	77H	TL	<b>87-4596</b>
160/60R18 HD	70V	TL	<b>87-4192</b>	150/80B16 HD	77H	TL	<b>87-4597</b>
100/90-19 HD	61H	TL	<b>87-4587</b>	170/70-16	75H	TL	<b>87-4573</b>
110/90-19	62H	TL	<b>87-4564</b>	180/65B16 HD	81H	TL	<b>87-4599</b>
130/60B19 HD	67H	TL	<b>87-4606</b>	160/70-17 HD	79H	TL	<b>87-4601</b>
6.5-20 HD	77H	TL	<b>87-4200</b>	180/60B17	81V	TL	<b>87-4619</b>
80/90-21 HD	54H	TL	<b>87-4589</b>	200/55R17	78V	TL	<b>87-4578</b>
90/90-21	54H	TL	<b>87-4182</b>	140/70B18 HD	72H	TL	<b>87-4610</b>
120/70-21 HD	68V	TL	<b>87-4583</b>	150/70B18 HD	76H	TL	<b>87-4612</b>
130/60-23 HD	75H	TL	<b>87-4581</b>	180/55B18 HD	84H	TL	<b>87-4608</b>
120/50-26 HD	73H	TL	<b>87-4603</b>	240/40VR18	79V	TL	<b>87-4193</b>
140/40-30	57H	TL	<b>87-4580</b>				



## SR777 & SR777 H.D.

### REFLECTOR

Shinko 777 Reflector 777 H.D. Reflector tires are the next evolution in motorcycle tire technology. Almost completely unnoticeable until light hits the reflective material on the sidewall and then BAM ...the sidewall of the Shinko 777 Reflector tire lights up. Be Safe. Be Seen. 777 Reflector & 777 H.D Reflector tires are specifically designed for cruiser motorcycles and are available in many sizes to fit V-Twin and metric cruiser models.

- Reflective strip is built into the sidewall of the tire
- Reflective strip appears dark grey in the daytime
- Rubber compound formulated to provide maximum grip and comfort
- Confidence inspiring traction you can feel when accelerating, braking and cornering
- H.D. (Heavy Duty) version with reinforced carcass providing a more stable and planted feel
- H speed rated tubeless
- Aramid belted provides ample load capacity while also giving more stability
- Unleash the handling potential of you cruiser motorcycle



Reflector During Day



Reflector During Night

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
130/90B-16 HD	73H	TL	<b>87-4570</b>
130/80-17	65H	TL	<b>87-4558</b>
100/90-19 HD	61H	TL	<b>87-4801</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
170/80B-15 HD	83H	TL	<b>87-4559</b>
130/90B-16 HD	73H	TL	<b>87-4800</b>
150/80B-16 HD	69Q	TL	<b>87-4805</b>
180/65B-16 HD	81H	TL	<b>87-4809</b>





FRONT

REAR

## SR777 & SR777 H.D. WHITE WALL

Shinko SR777 & SR777 H.D. White Wall tires are specifically designed for the rider looking for the ultimate performance cruiser tire! The SR777 compound is formulated for maximum grip and control to inspire confidence! Available in a multitude of sizes to fit many V-Twin and metric cruiser models.

- Rubber compound formulated to provide maximum grip and comfort
- Vivid white sidewalls provide a classic look
- White walls available for many common V-Twin and metric cruiser fitment
- Tread design includes functional siping and grooves for superior traction in wet and dry riding conditions
- Confidence inspiring traction you can feel when accelerating, braking and cornering
- H.D. (Heavy Duty) version with reinforced carcass
- Aramid belted
- Unleash the handling potential of your cruiser motorcycle

Size	Load/ Speed Rating	TT/ TL	WPS#	Size	Load/ Speed Rating	TT/ TL	WPS#
<b>FRONT</b>				<b>REAR</b>			
130/90B16 HD	73H	TL	<b>87-4586</b>	150/90B15 HD	80H	TL	<b>87-4591</b>
150/80-16	71H	TL	<b>87-4605</b>	170/80B15 HD	83H	TL	<b>87-4593</b>
120/90-17	64H	TL	<b>87-4618</b>	180/70B15 HD	82H	TL	<b>87-4615</b>
130/80-17	65H	TL	<b>87-4567</b>	130/90B16 HD	73H	TL	<b>87-4595</b>
140/80-17	69H	TL	<b>87-4562</b>	MU85B16 HD	77H	TL	<b>87-4569</b>
130/70B18 HD	69H	TL	<b>87-4617</b>	150/80B16 HD	77H	TL	<b>87-4598</b>
100/90-19 HD	61H	TL	<b>87-4588</b>	170/70-16	75H	TL	<b>87-4574</b>
130/60B19 HD	67H	TL	<b>87-4607</b>	180/65B16 HD	81H	TL	<b>87-4600</b>
90/90-21	54H	TL	<b>87-4565</b>	160/70-17 HD	79H	TL	<b>87-4602</b>
120/70-21 HD	68H	TL	<b>87-4584</b>	140/70B18 HD	72H	TL	<b>87-4611</b>
130/60-23 HD	75H	TL	<b>87-4582</b>	150/70B18 HD	76H	TL	<b>87-4613</b>
				180/55B18 HD	84H	TL	<b>87-4609</b>



## 230 TOUR MASTER

- Designed for long distance, high speed riding
- Aramid belted
- Staggered tread design offers a quiet ride with excellent handling
- Outstanding dry and wet weather performance
- Many sizes available with a V Speed Rating (149 MPH)

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
130/90-16	67V	TL	<b>87-4165</b>
150/80-16	71H	TL	<b>87-4169</b>
120/90-17	64H	TL	<b>87-4168</b>
150/80-17	72H	TL	<b>87-4166</b>
100/90-18	56V	TL	<b>87-4160</b>
110/90-18	61V	TL	<b>87-4162</b>
120/90-18	65V	TL	<b>87-4164</b>
100/90-19	57V	TL	<b>87-4161</b>
110/90-19	62V	TL	<b>87-4163</b>
80/90-21	48H	TL	<b>87-4167</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
130/90-15	66V	TL	<b>87-4171</b>
140/90-15	76V	TL	<b>87-4175</b>
150/90-15	80V	TL	<b>87-4176</b>
170/80-15	83V	TL	<b>87-4177</b>
180/70-15	76H	TL	<b>87-4178</b>
130/90-16	73V	TL	<b>87-4172</b>
140/90-16	77V	TL	<b>87-4179</b>
150/80-16	71H	TL	<b>87-4130</b>
130/90-17	74V	TL	<b>87-4173</b>
120/90-18	71V	TL	<b>87-4170</b>
130/90-18	69V	TL	<b>87-4174</b>



## 712

- Designed for mileage and performance
- Staggered tread pattern provides excellent wet weather performance
- Tubeless

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/80-16	60H	TL	<b>87-4143</b>
100/90-18	56H	TL	<b>87-4140</b>
3.00-18	55H	TL	<b>87-4157</b>
100/90-19	57H	TL	<b>87-4141</b>
110/90-19	61H	TL	<b>87-4142</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
140/90-15	70H	TL	<b>87-4154</b>
130/90-16	67H	TL	<b>87-4152</b>
130/90-17	68H	TL	<b>87-4153</b>
150/70-17	69H	TL	<b>87-4155</b>
3.50-18	60H	TL	<b>87-4158</b>
100/90-18	56H	TL	<b>87-4156</b>
110/90-18	61H	TL	<b>87-4150</b>
120/90-18	65H	TL	<b>87-4151</b>





611  
Front718  
Rear

## 611 AND 718

- The 611 front and 718 rear feature directional tread designs
- Paired together they make an ideal matched set with excellent adhesion in both wet and dry conditions
- Aramid belt for added stability
- Tubeless

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT 611</b>			
MT90-16	71H	TL	<b>87-4120</b>
MM90-19	61H	TL	<b>87-4121</b>
MH90-21	56H	TL	<b>87-4122</b>
<b>REAR 718</b>			
MT90-16	74H	TL	<b>87-4125</b>



## 250

- Modern directional tread designed for excellent wet weather traction and long stable mileage
- Front tire has single radius profile for light steering and increased stability
- Rear tire uses dual radius profile design for a larger foot print increasing traction and mileage
- Advanced Dupont™ KEVLAR® belting provides high load stability
- Available in BLACKWALL and WHITEWALL (W/W)
- Tubeless

Size	Load/Speed Rating	Sidewall	TT/TL	WPS#
<b>FRONT</b>				
MT90-16	73H		TL	<b>87-4100</b>
MT90-16	73H	WW	TL	<b>87-4101</b>
MJ90-19	56H		TL	<b>87-4103</b>
MH90-21	56H		TL	<b>87-4104</b>
<b>REAR</b>				
MT90-16	74H		TL	<b>87-4105</b>
MT90-16	74H	WW	TL	<b>87-4106</b>

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont Nemours and Company.



## SR733/734/735 SERIES

- Popular touring/cruiser tread pattern
- Tubeless

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT SR733</b>			
130/70-18	63H	TL	<b>87-4470</b>
100/90-19	57H	TL	<b>87-4471</b>
<b>REAR SR734</b>			
130/90-15	66P	TL	<b>87-4475</b>
150/80-15	70S	TL	<b>87-4476</b>
170/80-15	77H	TL	<b>87-4477</b>
160/80-16	75H	TL	<b>87-4478</b>
<b>FRONT/REAR SR735</b>			
110/90-16	59S	TL	<b>87-4479</b>







## SE890 JOURNEY TOURING RADIAL

- Designed for larger touring bikes and cruisers
- Specially designed tread efficiently disperses water in wet road conditions
- Tread compound designed for optimal grip and mileage
- Aramid belted, radial construction
- Economically priced without sacrificing quality
- Excellent ride quality and load carrying capability
- Tubeless design

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
150/80R17	72H	TL	<b>87-4660</b>
130/70R18	63H	TL	<b>87-4661</b>
<b>REAR</b>			
160/80R16	81H	TL	<b>87-4665</b>
180/60R16	74H	TL	<b>87-4666</b>
180/70R16	77H	TL	<b>87-4667</b>
200/55R16	77H	TL	<b>87-4668</b>

## CLASSIC 240

- Modern construction & performance... classic design
- Compounded for high mileage
- 90% aspect ratio, classic profile and tread pattern
- Dupont™ KEVLAR® belting offsets tread distortion for better grip and durability
- Available in BLACK WALL, WHITE WALL (W/W) and DOUBLE STRIPE WHITE WALL (Double W/W)
- 100/90-19 & 100/90-19 W/W are Tubeless... all others are Tube Type

Size	Load/Speed Rating	Sidewall	TT/TL	WPS#
<b>FRONT</b>				
100/90-19	63H		TL	<b>87-4115</b>
100/90-19	63H	WW	TL	<b>87-4116</b>
<b>FRONT/REAR</b>				
MT90-16	74H		TT	<b>87-4110</b>
MT90-16	74H	WW	TT	<b>87-4111</b>
MT90-16	74H	DWS	TT	<b>87-4112</b>

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont Nemours and Company.







## 270 SUPER CLASSIC

- Now available in a 21" front
- The classic full aspect ratio sawtooth design
- Nylon carcass for extended wear with a classic appearance
- Available in BLACK WALL and WHITE WALL (W/W)
- Tube type

Size	Load/Speed Rating	Sidewall	TT/TL	WPS #
<b>FRONT</b>				
4.00-19	61H		TT	<b>87-4622</b>
4.00-19	61H	WW	TT	<b>87-4623</b>
3.00-21	57H		TT	<b>87-4633</b>
3.00-21	57H	WW	TT	<b>87-4634</b>
<b>FRONT/REAR</b>				
5.00-16	69S		TT	<b>87-4620</b>
5.00-16	69S	WW	TT	<b>87-4621</b>
4.00-18	64H		TT	<b>87-4624</b>
4.00-18	64H	WW	TT	<b>87-4626</b>
4.50-18	70H		TT	<b>87-4628</b>
4.50-18	70H	WW	TT	<b>87-4632</b>







***SPORT/SPORT TOURING***

## 016 VERGE 2X DUAL COMPOUND RADIAL

Experience the new standard in motorcycle tires from Shinko, the DUAL COMPOUND 016 VERGE 2X! With dual compound technology and Zero Degree JLSB (Joint Less Steel Belting) you'll get the best of both worlds, superior traction when needed, AND mileage. Tread sipes added for better wet grip and even wear. The full steel belted front and rear tires provide high speed stability and confidence in corners

- The Ultimate Sport/Touring tire
- Zero degree steel-belted sport radial tire featuring JLSB (Joint Less Steel Belting) state-of-the-art technology for added stability and carcass strength
- Best of both worlds with a true DUAL COMPOUND design providing superior traction AND mileage
- Siping allows for added wet traction and longevity
- Tread profile designed for quick transitions and more lean angle

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/60ZR17	(55W)	TL	<b>87-4083</b>
120/70ZR17	(58W)	TL	<b>87-4084</b>
<b>REAR</b>			
160/60ZR17	(69W)	TL	<b>87-4085</b>
180/55ZR17	(73W)	TL	<b>87-4097</b>
190/50ZR17	(73W)	TL	<b>87-4098</b>
190/55ZR17	(75W)	TL	<b>87-4086</b>
200/50ZR17	(75W)	TL	<b>87-4099</b>







## 011 VERGE RADIAL

- Sport/Touring tire offering performance combined with extended tread life
- Specifically designed for today's Sport/Touring rider
- Rear tires feature Zero Degree JLSB (Joint-Less Steel Belted) state-of-the-art technology for added stability and strength
- Front tires are Aramid belted for enhanced high speed performance
- Tread area designed for enhanced high speed cornering

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/60ZR17	(55W)	TL	<b>87-4080</b>
120/70ZR17	(58W)	TL	<b>87-4081</b>
140/75VR17	(67V)	TL	<b>87-4079</b>
120/70ZR18	(59W)	TL	<b>87-4082</b>
130/60VR23	65V	TL	<b>87-4088</b>
<b>REAR</b>			
150/80ZR16	(71W)	TL	<b>87-4090</b>
160/60ZR17	(69W)	TL	<b>87-4091</b>
170/60ZR17	(72W)	TL	<b>87-4092</b>
180/55ZR17	(73W)	TL	<b>87-4093</b>
190/50ZR17	(73W)	TL	<b>87-4094</b>
200/50ZR17	(75W)	TL	<b>87-4095</b>
200/55VR17	(78V)	TL	<b>87-4087</b>
200/50VR18	76V	TL	<b>87-4096</b>
300/35VR18	(87V)	TL	<b>87-4089</b>







## SMOKE BOMB

- Looks and performs just like an 005 Advance!!
- Produces colored smoke during a burnout (tires appearance is black)
- Designed for closed course / exhibition use only

- **NHS**

### FOR EXHIBITION USE ONLY.

Protect all painted surfaces from possible paint damage.

Size	Load/Speed Rating	TT/TL	Blue	Red
180/55ZR17	73W	TL	<b>87-4670B</b>	<b>87-4670R</b>
190/50ZR17	73W	TL	<b>87-4671B</b>	<b>87-4671R</b>

## 009 RAVEN RADIAL

- Specifically designed to meet the demand for long life, high performance radial tires
- Provides superior riding comfort, while the tread compound gives high grip on both wet and dry roads
- W speed rated (168 mph), Aramid belted, DOT approved
- Highest tread life of Shinko sport performance radials

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/60ZR17	55W	TL	<b>87-4040</b>
120/70ZR17	58W	TL	<b>87-4041</b>
<b>REAR</b>			
160/60ZR17	69W	TL	<b>87-4045</b>
170/60ZR17	72W	TL	<b>87-4046</b>
180/55ZR17	73W	TL	<b>87-4047</b>
190/50ZR17	73W	TL	<b>87-4048</b>
200/50ZR17	75W	TL	<b>87-4049</b>







## 003 STEALTH RADIAL

- Slick/dimple design, great for production and drag racing, and serious sport riding
- Soft compound for rapid warmup, gives racing slick like performance
- W speed rated (168 mph), Aramid belted, DOT approved
- Available in Ultra-Soft compound - great for drag racing and track use
- Due to the soft compound of this tire, it is not for use on dynamometers!

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/60ZR17	55W	TL	<b>87-4000</b>
120/60ZR17 Ultra-Soft	55W	TL	<b>87-4000U</b>
120/70ZR17	58W	TL	<b>87-4001</b>
120/70ZR17 Ultra-Soft	58W	TL	<b>87-4001U</b>
<b>REAR</b>			
150/60ZR17	66W	TL	<b>87-4004</b>
160/60ZR17	69W	TL	<b>87-4003</b>
170/60ZR17	72W	TL	<b>87-4006</b>
180/55ZR17	73W	TL	<b>87-4007</b>
180/55ZR17 Ultra-Soft	73W	TL	<b>87-4007U</b>
190/50ZR17	73W	TL	<b>87-4008</b>
190/50ZR17 Ultra-Soft	73W	TL	<b>87-4008U</b>
200/50ZR17	75W	TL	<b>87-4009</b>
200/50ZR17 Ultra-Soft	75W	TL	<b>87-4009U</b>
180/55ZR18	74W	TL	<b>87-4005</b>

## 010 APEX RADIAL

- Tread designed for serious sport or sport touring riding
- Rear tires feature Zero Degree JLSB (Joint-Less Steel Belted) state-of-the-art technology for added stability and carcass strength
- Front tires are Aramid belted for enhanced high speed performance
- Tread area designed for enhanced high speed cornering

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/60ZR17	(55W)	TL	<b>87-4060</b>
120/70ZR17	(58W)	TL	<b>87-4061</b>
<b>REAR</b>			
150/60ZR17	(66W)	TL	<b>87-4070</b>
160/60ZR17	(69W)	TL	<b>87-4071</b>
170/60ZR17	(72W)	TL	<b>87-4072</b>
180/55ZR17	(73W)	TL	<b>87-4073</b>
190/50ZR17	(73W)	TL	<b>87-4074</b>
190/55ZR17	(75W)	TL	<b>87-4075</b>
200/50ZR17	(75W)	TL	<b>87-4076</b>







## SR880 / 881 RADIAL

- All weather tread design, works well in wet and dry road conditions
- Intermediate compound offers good traction and tire life
- Aramid belted, DOT approved
- Sizes for CBR 250/300, Ninja 300, R3, KTM 390

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT 880</b>			
130/60ZR16	58W	TL	<b>87-4680</b>
110/70VR17	54V	TL	<b>87-4681</b>
<b>REAR 881</b>			
160/60ZR16	68W	TL	<b>87-4685</b>
140/70VR17	66V	TL	<b>87-4686</b>



## SR740/741 SERIES

- Specially designed tread efficiently disperses water in wet road conditions
- Tubeless

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT SR740</b>			
100/80-16	50H	TL	<b>87-4462</b>
110/70-17	54H	TL	<b>87-4460</b>
110/80-17	58V	TL	<b>87-4461</b>
<b>REAR SR741</b>			
130/80-16	64H	TL	<b>87-4467</b>
130/70-17	62H	TL	<b>87-4468</b>
150/70-17	69H	TL	<b>87-4465</b>
140/70-18	63V	TL	<b>87-4466</b>

## 005 ADVANCE RADIAL

- Large block type tread pattern with excellent braking, cornering and acceleration characteristics
- Specially designed tread grooves help to dissipate water efficiently on wet surfaces
- Rubber compound formulated to improve grip and durability
- Dupont™ Kevlar® belted to enhance high speed performance

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/60ZR17	55W	TL	<b>87-4011</b>
120/70ZR17	58W	TL	<b>87-4010</b>
130/70VR18	63V	TL	<b>87-4012</b>
120/70V21	62V	TL	<b>87-4013</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
160/60ZR17	69W	TL	<b>87-4014</b>
170/60ZR17	72W	TL	<b>87-4015</b>
180/55ZR17	73W	TL	<b>87-4016</b>
190/50ZR17	73W	TL	<b>87-4017</b>
200/50ZR17	75W	TL	<b>87-4018</b>
240/40VR18	79V	TL	<b>87-4019</b>

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont Nemours and Company.







## 006 PODIUM RADIAL

- Designed for high performance on either wet or dry surfaces
- Streamlined tread pattern reduces rotating resistance while improving water drainage
- Smooth shoulder profile insures superior grip and exceptional stability at all lean angles
- Aramid belted
- Wide range of fitment options

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
130/70ZR16	61W	TL	<b>87-4020</b>
110/70R17	54V	TL	<b>87-4021</b>
120/60ZR17	55W	TL	<b>87-4022</b>
120/70ZR17	58W	TL	<b>87-4023</b>
130/60ZR17	59W	TL	<b>87-4024</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
140/60R17	63V	TL	<b>87-4030</b>
150/60R17	66V	TL	<b>87-4031</b>
160/60ZR17	69W	TL	<b>87-4032</b>
170/60ZR17	72W	TL	<b>87-4033</b>
180/55ZR17	73W	TL	<b>87-4034</b>
140/60R18	64V	TL	<b>87-4036</b>
150/60R18	67V	TL	<b>87-4037</b>
170/60R18	73V	TL	<b>87-4038</b>







***DRAG / RACE / SPECIALTY***









## FLAT TRACK SR267/268

Shinko Flat Track tires are designed and tested to perform at the highest level of the sport. The SR267/268 is available in 3 different compounds to give you the best tire for any track. GET "SLIDEWAYS"!!!

- Available in Soft-Medium-Hard compounds
- Proven performance
- DOT approved
- Tube Type

Size	Load/Speed Rating	TT/TL	Soft	Medium	Hard
<b>FRONT</b>					
130/80-19 (27.0 x 7.0-19)	67H	TT	<b>87-4750S</b>	<b>87-4750M</b>	<b>87-4750H</b>
<b>REAR</b>					
140/80-19 (27.5 x 7.5-19)	71H	TT	<b>87-4751S</b>	<b>87-4751M</b>	<b>87-4751H</b>
<b>JUNIOR FRONT/REAR</b>					
120/70-17	58M	TT	<b>87-4752S</b>		

## STEALTH-D

- Specifically designed for V-Twin Drag racing
- DOT approved
- Ultra-Soft compound for maximum traction
- Fits right onto your stock 16" wheel!!

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
150/80ZR16	71W	TL	<b>87-4002U</b>



## REACTOR II DRAG SLICK

- Wrinkle wall drag slick, for track use only
- Tread compound designed for maximum traction
- 26" x 7" x 17" size fits most sport bike rear wheels
- Recommended rim width 5½" to 7½"
- Track use only
- **NHS (Not for Highway Service)**

Size	WPS #
<b>REAR</b>	
26" x 7" - 17	<b>87-4656</b>



## 008 RACE TIRES

- Completely slick, soft compound tread
- Radial construction
- Aramid belted
- Recommended for multiple track use applications
- Excellent Super Moto tire
- **NHS (Not for Highway Service)**

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/60R17	55V	TL	<b>87-4051</b>
120/70R17	58V	TL	<b>87-4050</b>
<b>REAR</b>			
150/60R17	66V	TL	<b>87-4055</b>
160/60R17	69V	TL	<b>87-4056</b>
180/55R17	73V	TL	<b>87-4058</b>
190/50R17	73V	TL	<b>87-4059</b>







## HOOK-UP DRAG RADIAL

- Light weight extremely flexible carcass
- Softest street compound available from Shinko
- Tread pattern and profile designed specifically for the demands of drag racing
- Aramid belted, DOT approved, not intended for use on public roads or street use
- Combine with the Shinko 003 Stealth front tire for a matching tread pattern
- Due to the soft compound of this tire, it is not for use on dynamometers!

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
180/55ZR17	73W	TL	<b>87-4650</b>
190/50ZR17	73W	TL	<b>87-4651</b>
200/50ZR17	75W	TL	<b>87-4652</b>

## HOOK-UP PRO DRAG RADIAL

- The ultimate DOT drag tire.....Just got better!!
- Introducing the new HOOK-UP PRO! All of the great features of the original Hook-Up, but lighter, faster and now even better at the top-end of the track! Competition-developed design allows for more horsepower to be used throughout the run due to a larger contact patch at high speed. Enhanced carcass resists distortion, chunking, and the stresses of centrifugal force to maintain a more constant footprint.
- Due to the soft compound of this tire, it is not for use on dynamometers!

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
190/50ZR17	73W	TL	<b>87-4651P</b>
200/50ZR17	75W	TL	<b>87-4652P</b>







***DUAL SPORT***

## E804 / E805

### ADVENTURE TRAIL SERIES

- 40% on-road 60% off-road
- Latest in Big-Block Technology
- Superior on-road handling and mileage
- Stable sidewalls for soft surfaces
- DOT approved
- M+S = Mud and Snow Rated

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT E804</b>			
100/90-19	57S	TT	<b>87-4703</b>
110/80-19	59Q	TL	<b>87-4700</b>
110/80R19	59R	TL	<b>87-4698</b>
120/70R19	60H	TL	<b>87-4708</b>
90/90-21	54T	TL	<b>87-4702</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR E805</b>			
150/80B16	77H	TL	<b>87-4697</b>
130/80-17	65T	TL	<b>87-4704</b>
140/80-17	69Q	TT	<b>87-4706</b>
150/70-17	69Q	TL	<b>87-4701</b>
150/70R17	69R	TL	<b>87-4699</b>
170/60R17	72H	TL	<b>87-4709</b>
120/90-18	65R	TT	<b>87-4707</b>
150/70B18	70Q	TL	<b>87-4705</b>







## E804 / E805 ADVENTURE TRAIL REFLECTOR SERIES

Shinko introduces their REFLECTOR side wall technology to the popular E804/E805 Adventure Trail tires. Almost completely unnoticeable until light hits the reflective material on the sidewall and then boom ...the sidewall of the Reflector tire lights up. Be Safe. Be Seen.

- Same outstanding performance as the standard 804/805 with added safety in mind
- Reflective material is built into the sidewall of the tire
- The only ADV tire on the market with a reflective sidewall
- Designed as a 40% On-Road 60% Off-Road tire
- DOT approved
- M+S = Mud and Snow Rated

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT E804</b>			
110/80-19	59Q	TL	<b>87-4714</b>
90/90-21	54T	TL	<b>87-4715</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR E805</b>			
130/80-17	65T	TL	<b>87-4716</b>
140/80-17	65R	TT	<b>87-4717</b>
150/70-17	69Q	TL	<b>87-4718</b>
150/70B18	70Q	TL	<b>87-4719</b>

## 705 ADVENTURE TOURING

- Versatile tread pattern provides excellent wet and dry weather adhesion and smooth running on the highway
- All-round rubber compound for a wide spectrum of weather and street/terrain conditions
- Designed as a 70% On-Road, 30% Off-Road tire
- Great traction, even Off-Road, thanks to the dirt-oriented tread design
- DOT approved
- 150/70R18 rear tires features state-of-the-art Zero Degree JLSB (Joint-Less Steel Belting) technology for added stability and strength
- **M+S = Mud and Snow Rated**

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/70R17	58H	TL	<b>87-4529</b>
110/80-19	59Q	TL	<b>87-4527</b>
110/80R19	59H	TL	<b>87-4535</b>
120/70R19	60H	TL	<b>87-4524</b>
90/90-21	54H	TL	<b>87-4528</b>

<b>REAR</b>			
150/70R17	69H	TL	<b>87-4536</b>
170/60R17	72V	TL	<b>87-4530</b>
150/70VR18	70V	TL	<b>87-4537</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
120/90-17	64H	TT	<b>87-4520</b>
130/80-17	65H	TL	<b>87-4521</b>
130/90-17	68H	TT	<b>87-4522</b>
140/80-17	69H	TT	<b>87-4523</b>
4.10-18	59P	TT	<b>87-4525</b>
120/80-18	62H	TT	<b>87-4526</b>







## 700 SERIES

- Aggressive tread pattern with deep lug construction for off-road performance
- Rounded profile and side knobs designed for cornering stability on the street
- Heavy duty 4-ply carcass for durability
- DOT approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
3.00-21	51S	TL	<b>87-4390</b>
<b>REAR</b>			
4.60-17	62P	TT	<b>87-4395</b>
5.10-17	67P	TL	<b>87-4396</b>
4.60-18	63P	TT	<b>87-4397</b>
130/80-18	66P	TL	<b>87-4398</b>

## SR241 SERIES

- A versatile performer with a tough nylon carcass
- Raised dimpled knobs work well in a variety of terrain
- Narrow knobby configuration means less of an environmental foot print on the trail
- 4 ply rated tube type
- DOT approved
- Not intended for extended highway use
- All sizes will work for front or rear fitment

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
3.00-12	47J	TT	<b>87-4451</b>
2.75-14	35P	TT	<b>87-4440</b>
2.50-15	34L	TT	<b>87-4452</b>
3.00-16	43P	TT	<b>87-4441</b>
2.50-17	38L	TT	<b>87-4442</b>
2.75-17	47J	TT	<b>87-4443</b>
3.00-17	45P	TT	<b>87-4444</b>
2.75-18	42P	TT	<b>87-4453</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR (CONT'D...)</b>			
3.00-18	47P	TT	<b>87-4454</b>
3.50-18	56P	TT	<b>87-4445</b>
4.00-18	64P	TT	<b>87-4450</b>
2.75-19	43P	TT	<b>87-4446</b>
3.50-19	57P	TT	<b>87-4449</b>
2.75-21	45P	TT	<b>87-4447</b>
3.00-21	51P	TT	<b>87-4448</b>



## 244 SERIES

- Adventure Trail
- Dual purpose street and trail design
- Designed to be equally at home on dirt and pavement
- Tube Type
- DOT approved
- All sizes designed for front or rear fitment

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
2.75-14	35P	TT	<b>87-4400</b>
3.00-16	45P	TT	<b>87-4401</b>
2.50-17	38L	TT	<b>87-4402</b>
3.00-17	50P	TT	<b>87-4760</b>
4.60-17	68S	TT	<b>87-4766</b>
5.10-17	67P	TT	<b>87-4405</b>
3.00-18	52L	TT	<b>87-4761</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR (CONT'D...)</b>			
3.50-18	62P	TT	<b>87-4764</b>
4.10-18	65S	TT	<b>87-4765</b>
4.60-18	69S	TT	<b>87-4767</b>
5.10-18	69P	TT	<b>87-4410</b>
2.75-19	43P	TT	<b>87-4411</b>
2.75-21	52P	TT	<b>87-4762</b>
3.00-21	57L	TT	<b>87-4763</b>







## TRAIL PRO 255 RADIAL

**CAUTION:** The 255 and 241 Series tires are D.O.T. approved tires but are not recommended for commuter/continuous highway use. They are tires for serious off road and trails applications and can be legally used "on highway" to connect off road trail heads. For dual sport use, we recommend the Shinko 244, 700 or 705 series tires.

- Super soft compound with a highly flexible radial carcass, provides excellent grip on rocks and other slick terrain
- Lightweight, reduces un-sprung weight for improved off-road performance and maneuverability
- Works excellent in gnarly technical single-track terrain
- Available in 18" and 19" rear radial sizes
- Tubeless
- DOT approved
- Not intended for extended highway use

Size	Load/Speed Rating	TT/TL	WPS #
<b>REAR</b>			
110/90R18	61L	TL	<b>87-4290</b>
120/90R18	65M	TL	<b>87-4292</b>
110/80R19	59L	TL	<b>87-4291</b>
120/80R19	63M	TL	<b>87-4293</b>



## SR428 SERIES

- 4 ply rated nylon carcass
- Sizes to fit the **TW200, Grom & Z125**
- DOT approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
120/70-12	51J	TL	<b>87-4480</b>
130/80-18	66P	TT	<b>87-4483</b>
<b>REAR</b>			
130/70-12	56J	TL	<b>87-4481</b>
180/80-14	78P	TT	<b>87-4482</b>



## 421 MINI BIKE TRAIL

- Tough nylon carcass
- Open tread pattern cleans out well in muddy conditions
- DOT approved
- Not intended for extended highway use
- Tube type

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
3.50-8	46J	TT	<b>87-4420</b>
4.00-8	55J	TT	<b>87-4421</b>
3.00-10	42J	TT	<b>87-4422</b>
3.50-10	51J	TT	<b>87-4423</b>







***SMALL BORE***

## SR723

- Tubeless
- DOT Approved
- Available in white sidewall
- Common Scooter, GROM, Z125 and Rukus sizes available

Size	Load/Speed Rating	Sidewall	TT/TL	WPS#
<b>FRONT</b>				
120/70-10	54P		TL	<b>87-4264</b>
120/70-10	54P	WW	TL	<b>87-4265</b>
110/70-11	45P		TL	<b>87-4266</b>
110/70-11	45P	WW	TL	<b>87-4267</b>
120/70-12	58P		TL	<b>87-4260</b>
120/70-12	58P	WW	TL	<b>87-4261</b>
<b>REAR</b>				
130/70-12	62P		TL	<b>87-4262</b>
130/70-12	62P	WW	TL	<b>87-4263</b>
<b>FRONT/REAR</b>				
110/70-12	47P	WW	TL	<b>87-4258</b>
140/70-12	65P	WW	TL	<b>87-4259</b>







## SR400

- Front or rear fitment, tube type
- DOT approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
2.50-10	33J	TT	<b>87-4225</b>



## SR425

- 4 ply rated nylon carcass
- Tubeless (unless noted)
- DOT approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
3.00-10	42J	TL	<b>87-4270</b>
3.50-10	51J	TL	<b>87-4271</b>
110/80-10	58J	TL	<b>87-4275</b>
<b>REAR</b>			
90/90-10	50J	TL	<b>87-4272</b>
100/80-10	53J	TL	<b>87-4273</b>
100/90-10	56J	TL	<b>87-4274</b>
<b>FRONT/REAR</b>			
120/90-10	66J	TL	<b>87-4276</b>
130/70-10	52J	TL	<b>87-4277</b>
130/90-10	70J	TL	<b>87-4278</b>
130/60-13	53J	TL	<b>87-4279</b>



## SR426

- Great replacement tire for Yamaha Zuma
- DOT approved
- Tubeless, 4 ply construction

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
120/90-10	66J	TL	<b>87-4190</b>
130/90-10	70J	TL	<b>87-4191</b>



## SR429

- Tubless 4-ply rating
- DOT Approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
120/70-13	53L	TL	<b>87-4230</b>
130/60-13	53L	TL	<b>87-4231</b>

## SR007

- Tubeless 4-ply rating
- DOT Approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT</b>			
110/90-12	64P	TL	<b>87-4210</b>
110/70-12	47P	TL	<b>87-4213</b>
<b>REAR</b>			
130/90-10	70J	TL	<b>87-4216</b>
120/70-11	50L	TL	<b>87-4214</b>
130/70-12	62P	TL	<b>87-4211</b>
140/70-12	60P	TL	<b>87-4212</b>



## SR550

- Tube type (unless noted), 4-ply rating
- DOT Approved
- J Speed rating (62 mph)
- Available in white wall only

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
3.50-8	46J	TT	<b>87-4250</b>
4.00-8	55J	TT	<b>87-4251</b>
3.00-10	50J	TT	<b>87-4252</b>
3.50-10	59J	TT	<b>87-4253</b>
3.50-10	59J	TL	<b>87-4254</b>



## SR009

- Tubeless 4-ply rating
- DOT Approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
3.50-10	51J	TL	<b>87-4220</b>



## SR560

- Tube type 4-ply rating
- DOT Approved
- J Speed rating (62 mph)

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
80/90-10	44J	TL	<b>87-4240</b>
90/90-10	50J	TL	<b>87-4241</b>







## SR567

- 4 ply rated nylon carcass
- Tubeless DOT approved
- Available in many popular sizes

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT SR567</b>			
110/90-12	64P	TL	<b>87-4280</b>
110/90-13	56P	TL	<b>87-4281</b>
120/70-13	53P	TL	<b>87-4282</b>
120/70-14	55S	TL	<b>87-4283</b>
120/80-14	58S	TL	<b>87-4284</b>
120/70-15	56S	TL	<b>87-4287</b>
120/70-16	57S	TL	<b>87-4288</b>
110/70-16	52S	TL	<b>87-4285</b>
110/80-16	55S	TL	<b>87-4286</b>



## SR568

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR SR568</b>			
130/70-12	62P	TL	<b>87-4500</b>
130/60-13	60P	TL	<b>87-4501</b>
130/70-13	63P	TL	<b>87-4502</b>
140/60-13	63P	TL	<b>87-4503</b>
150/70-13	64S	TL	<b>87-4504</b>
140/60-14	64S	TL	<b>87-4505</b>
150/70-14	66S	TL	<b>87-4506</b>
160/60-14	65H	TL	<b>87-4511</b>
160/60-15	67H	TL	<b>87-4512</b>
100/80-16	50P	TL	<b>87-4507</b>
120/80-16	60P	TL	<b>87-4508</b>
130/80-16	64P	TL	<b>87-4509</b>
140/70-16	65S	TL	<b>87-4510</b>



## SR704

- Moped Tire
- Tough nylon carcass
- 4 ply rated DOT approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
2.25-17	33L	TT	<b>87-4540</b>



## SR714

- Tube type 4-ply rating
- DOT Approved
- Moped fitment

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT/REAR</b>			
2.25-16	31L	TT	<b>87-4550</b>
80/80-16	45P	TT	<b>87-4430</b>
90/80-16	51P	TT	<b>87-4431</b>









**OFFROAD**



# FRONT TIRES

## TERRAIN GUIDE

FRONT TIRES - OFFROAD / ENDURO				
MODEL	MUD / SAND	SOFT	INTERMEDIATE	HARD
540				
525				
546				
216MX				
520				
504				
502				



# REAR TIRES

## TERRAIN GUIDE

REAR TIRES - OFFROAD / ENDURO / CHEATER

MODEL	MUD / SAND	SOFT	INTERMEDIATE	HARD
540				
525				
525 CHEATER				
546				
216MX				
216SX				
523				
505				
505 CHEATER				
520				
500				

## 216MX SERIES (FRONT)

- Extreme Offroad / Enduro / Desert tire
- Split tread pattern cleans out well and offers precise point and go control
- Proven for years in Europe's Erzberg, Romaniacs, and other extreme Enduro events
- Recently proven a top performer in the Baja 1000
- 90/100-21 "Fat Tyre" 216 MX
  - Taller-Fuller profile navigates through rocks, trees, and square edge terrain with ease
- FIM approved 13mm lug height
- DOT approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>FRONT ALL AROUND</b>			
80/100-21	51R	TT	<b>87-4730</b>
90/90-21	54R	TT	<b>87-4731</b>
<b>FRONT FAT TYRE</b>			
90/100-21	57R	TT	<b>87-4732</b>
<b>FRONT FAT TYRE CHEATER</b>			
90/100-21	57R	TT	<b>87-4732S</b>



216MX  
80/100-21

216MX  
90/90-21

216MX  
Fat Tyre





505

525

## 505, 525 HYBRID CHEATER

- Hybrid Cheater Enduro / Extreme single track trail tire find traction in the most extreme conditions
- The Cheater Hybrids a soft sticky trials style rubber compound on a moto-style carcass
- Tread design and unique rubber compound works well in a wide variety of soil conditions
- Where the Trials tire falls short in braking and lose soil conditions, the 505 & 525 Cheater bridge that gap to make the Ultimate Hybrid off-road tires
- "It's almost like cheating" The 505 Cheater shines in dry, harder conditions and the 525 has an open tread pattern that shines in soft/loose and loamy terrain
- Adds confidence even in the most demanding terrain
- Available in popular 18" and 19" sizes
- **NHS (Not for Highway Service)**

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
110/100-18	64M	TT	<b>87-4361S</b>
120/100-18	68M	TT	<b>87-4366S</b>
110/90-19	62M	TT	<b>87-4363S</b>
120/90-19	66M	TT	<b>87-4364S</b>

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR</b>			
90/100-16	51M	TT	<b>87-4383S</b>
110/100-18	64M	TT	<b>87-4326S</b>
120/100-18	68M	TT	<b>87-4382S</b>
110/90-19	62M	TT	<b>87-4328S</b>
120/90-19	66M	TT	<b>87-4381S</b>

## 520 SERIES

(INTERMEDIATE/HARD)

- Directional tread design works well in intermediate and hard terrain
- Reinforced knobs resist tearing and chunking
- Tire designed with a high carbon compound, increasing wear life and minimizing knob edge tear/wear
- **NHS (Not for Highway Service)**

Size	Load/Speed Rating	TT/TL	WPS #
<b>FRONT</b>			
2.50-10 (60/100-10)	33J	TT	<b>87-4202</b>
2.50-12 (60/100-12)	33J	TT	<b>87-4204</b>
70/100-17	40M	TT	<b>87-4335</b>
70/100-19	42M	TT	<b>87-4336</b>
80/100-21	51M	TT	<b>87-4331</b>
<b>REAR</b>			
2.75-10 (70/100-10)	38J	TT	<b>87-4203</b>
2.50-12 (60/100-12)	33J	TT	<b>87-4204</b>
90/100-14	49M	TT	<b>87-4330</b>
110/100-18	64M	TT	<b>87-4333</b>
120/100-18	68M	TT	<b>87-4334</b>
120/100-18 DC (Dual Compound)	68M	TT	<b>87-4338</b>
100/90-19	57M	TT	<b>87-4337</b>
110/90-19	62M	TT	<b>87-4332</b>



520  
Front

520  
Rear





## 216MX SERIES (REAR)

- Industry leading carcass technology providing a lightweight, flexible and durable tire design
- Ultimate Enduro performance tire with unmatched traction in the toughest terrain
- Available in two different rubber compound options:
- MX version features the all-around Enduro "firm" rubber compound
- SX version features an ultra-soft rubber compound for extreme grip on the toughest terrain
- Open tread design clears out well
- FIM approved 13mm lug height
- DOT approved

Size	Load/Speed Rating	TT/TL	WPS#
<b>REAR MX</b>			
110/100-18	64R	TT	<b>87-4742</b>
120/100-18	68R	TT	<b>87-4744</b>
140/80-18	70R	TL	<b>87-4740</b>
110/90-19	64R	TT	<b>87-4743</b>
120/90-19	66R	TT	<b>87-4745</b>
<b>REAR SX</b>			
140/80-18	70R	TL	<b>87-4741</b>

## 540 SERIES

### (MUD/SAND)

- For extremely soft terrain (mud/sand)
- Wide spaced knobs shed mud quickly
- Tall aggressive tread pattern offers increased traction in the nastiest conditions
- **NHS (Not for Highway Service)**

Size	Loa/Speed Rating	TT/TL	WPS #
<b>FRONT</b>			
70/100-17	40M	TT	<b>87-4300</b>
70/100-19	42M	TT	<b>87-4301</b>
80/100-21	51M	TT	<b>87-4302</b>
<b>REAR</b>			
90/100-14	49M	TT	<b>87-4310</b>
90/100-16	51M	TT	<b>87-4311</b>
100/100-18	59M	TT	<b>87-4315</b>
110/100-18	64M	TT	<b>87-4316</b>
120/100-18	68M	TT	<b>87-4317</b>
100/90-19	57M	TT	<b>87-4312</b>
110/90-19	62M	TT	<b>87-4313</b>
120/90-19	66M	TT	<b>87-4314</b>



540  
Front

540  
Rear





546  
Front

546  
Rear

## 546 SERIES

### (SOFT/INTERMEDIATE)

#### FRONT TIRE FEATURES:

- Front knobs use a 45° pattern for a better biting edge when cornering and braking stability
- Tall knobs offer excellent traction in soft to intermediate loam conditions
- 90/100 sizing features a taller side wall to prevent pinch flats in roots and rocky conditions. Excellent choice for Off-Road applications
- 80/100 sizing feature lower profile sidewall for more precise cornering and less sidewall flex
- **NHS (Not for Highway Service)**

#### REAR TIRE FEATURES:

- Works well in soft to intermediate terrain conditions
- Tall wide spaced knobs offer great self cleaning to provide excellent straight line traction on softer conditions
- Rubber compound offers excellent durability for long tread life
- **NHS (Not for Highway Service)**

Size	Load/Speed Rating	TT/TL	WPS #
<b>FRONT</b>			
70/100-17	40M	TT	<b>87-4710</b>
70/100-19	42M	TT	<b>87-4711</b>
80/100-21	51M	TT	<b>87-4712</b>
90/100-21	57M	TT	<b>87-4713</b>
<b>REAR</b>			
90/100-14	49M	TT	<b>87-4725</b>
90/100-16	51M	TT	<b>87-4726</b>
100/100-18 (125cc ONLY)	59M	TT	<b>87-4720</b>
110/100-18 (100/90-18)	64M	TT	<b>87-4721</b>
100/90-19 (125cc ONLY)	57M	TT	<b>87-4722</b>
110/90-19 (100/90-19)	62M	TT	<b>87-4723</b>
120/80-19 (110/90-19)	63M	TT	<b>87-4724</b>

## 524, 525 SERIES

### (SOFT/INTERMEDIATE)

- For soft to intermediate terrain
- Wide self-cleaning tread pattern
- Tall aggressive tread design
- Reinforced knobs resist tearing and chunking
- **NHS (Not for Highway Service)**

Size	Load/Speed Rating	TT/TL	WPS #
<b>FRONT 525</b>			
60/100-14	29M	TT	<b>87-4323</b>
<b>FRONT 524</b>			
70/100-19	42M	TT	<b>87-4322</b>
80/100-21	51M	TT	<b>87-4320</b>
<b>REAR 525</b>			
80/100-14	49M	TT	<b>87-4324</b>
90/100-14	49M	TT	<b>87-4329</b>
90/100-16	51M	TT	<b>87-4380</b>
100/100-18	59M	TT	<b>87-4325</b>
110/100-18	64M	TT	<b>87-4326</b>
120/100-18	68M	TT	<b>87-4382</b>
100/90-19	57M	TT	<b>87-4327</b>
110/90-19	62M	TT	<b>87-4328</b>
120/90-19	66M	TT	<b>87-4381</b>



524

525



504  
Front505  
Rear523  
Rear

## 504, 505, 523 SERIES (HARD)

- The Shinko 500, 502, 504, 505 and 523 Series tires are designed for hard terrain
- Featuring high carbon compound tread designs
- Maximizing tread wear and minimize tread knob tear/wear
- Offering great traction, braking and overall stability for enhanced control
- Reinforced knobs resist tearing and chunking while providing consistent grip
- **NHS (Not for Highway Service)**

Size	Load/Speed Rating	TT/TL	WPS #
<b>FRONT 504</b>			
120/70-12 Mobber	51P	TT	<b>87-4790</b>
80/100-21	51M	TT	<b>87-4355</b>
<b>REAR 505</b>			
130/70-12 Mobber	56P	TT	<b>87-4791</b>
100/100-18	59M	TT	<b>87-4360</b>
110/100-18	64M	TT	<b>87-4361</b>
120/100-18	68M	TT	<b>87-4366</b>
100/90-19	57M	TT	<b>87-4362</b>
110/90-19	62M	TT	<b>87-4363</b>
120/90-19	66M	TT	<b>87-4364</b>
<b>REAR 523</b>			
100/100-18	59M	TT	<b>87-4340</b>
110/100-18	64M	TT	<b>87-4341</b>
120/90-19	66M	TT	<b>87-4344</b>

## TIRE CONVERSION CHARTS

### SIZE CONVERSION TABLES:

Use these tables to convert your older style inch size to the new style metric sizing.

Metric	Alpha	Inch
FRONT STREET TIRES		
80/90	MH90	2.50/2.75
90/90	MJ90	2.75/3.00
100/80	MJ90	3.00
100/90	MM90	3.25/3.50
110/70	*	*
110/80	*	3.25/3.50
110/90	MN90	3.75/4.00
120/80	*	*
120/70	*	*
120/80	*	3.75/4.25/4.60
120/90	MR90	4.25/4.50
130/60	*	*
130/70	*	*
130/90	MT90	5.00/5.10

\* Should not change from OEM low profile sizing.

Metric	Alpha	Inch
REAR STREET TIRES		
110/90	MN90	3.75/4.25
120/80	MP85	4.50/4.75
120/90	MP85	4.50/4.75
130/70	*	*
130/80	*	5.00/5.10
130/90	MT90	5.00/5.10
140/60	*	*
140/70	*	*
140/80	*	5.50/6.00
140/90	MU90	5.50/6.00
150/70	*	*
150/80	MU85	6.00/6.25
150/90	MU85	6.00/6.25
160/60	*	*
160/70	*	*
160/80	*	*
170/60	*	*
170/80	*	*
180/50	*	*
180/55	*	*

### TIRE CONSTRUCTION

1. "Radial" describes a pneumatic tire structure in which the ply cord material extends from bead-to-bead crossing the center line of the tire at a 90 degree angle. The carcass is then secured with an inextensible belt positioned around the circumference of the tire.
2. "Bias Belted" describes a pneumatic Bias tire structure in which the carcass is restricted by a circumferential belt comprised of two or more layers of cord material.
3. "Bias" describes a pneumatic tire structure in which the ply cord material extends from bead-to-bead in varying (crisscross) angles, substantially less than 90 degrees to the center line of the tire.

### WARNING

- The information provided by WPS Inc. regarding tire and size information does not imply fitment or suggest interchangeable tire size compatibility with your specific motorcycle. Always consult your owner's manual to verify exact front and rear tire size including but not limited to; load rating, speed rating, tube type, construction (radial/bias), air pressure recommendations. Installation of incorrect tire size, construction type and load/speed ratings can cause handling issues which could result in personal injury or death.
- Only trained professionals should install (unmount/mount) and balance tires.
- All newly installed On-Road street motorcycle tires must be used with caution during the first 100 miles. Avoid excessive acceleration, breaking and steep lean angles during the "scrub-in" period of any new street tire.
- Check tire pressure regularly. Consult vehicles owner's manual or side wall of tire for air pressure (PSI) recommendations. Operating a tire below or above the recommended air pressure (PSI) can result in abnormal tire wear and could cause tire failure resulting in personal injury or death.
- Be sure to observe the rotation direction of front and rear tires.
- Motorcycle tires need to be replaced when the main tread patches meet the wear bar or TWI (Tread Wear Indicator).

## LOAD INDEX & SPEED RATING

This code, when present, appears after the size marking. The code comprises three characters, two numbers and a letter, e.g. 67 H, known as a service description. The two-digit number is a code for the maximum load carrying capacity of the tire. The letter is a maximum speed rating indicating the maximum speed at which the tire may be used with maximum load when the maximum listed inflation pressure is used. Shinko Does not recommend or endorse exceeding the safe, legal speed limit. The load index/speed symbol indicates the speed at which the tire can carry a load corresponding to its load index under conditions specified by the tire manufacturer.

LOAD INDEX								
Index	Kg.	Lbs.	Index	Kg.	Lbs.	Index	Kg.	Lbs.
30	106	234	53	206	454	77	412	908
31	109	240	54	212	467	78	425	937
32	112	245	55	218	490	79	437	963
33	115	254	56	224	494	80	450	992
34	118	260	57	230	507	81	462	1019
35	121	267	58	236	520	82	475	1047
36	125	276	59	243	536	83	487	1074
37	128	282	60	250	551	84	500	1102
38	128	282	61	257	567	85	515	1135
39	136	300	62	265	584	86	530	1168
40	140	309	63	272	600	87	545	1201
41	145	320	64	280	617	88	560	1235
42	150	331	65	290	640	89	580	1279
43	155	342	66	300	661	90	600	1323
44	160	353	67	307	677			
45	165	364	68	315	695			
46	170	375	69	325	717			
47	175	386	70	335	738			
48	180	397	71	345	761			
49	185	408	72	355	783			
50	190	419	73	365	805			
51	195	430	74	375	827			
52	200	441	75	387	853			
53	206	454	76	400	882			

Speed Code	km/h	(mph)	Speed Code	(mph)
SPEED RATINGS				
R	170	(106)	V	Speeds over 149 mph
S	180	(112)	Z	Speeds over 149 mph
H	210	(130)	W	Speed up to 168 mph

Learn more about motorcycle tires we have.