

BIG BIKE PARTS® INSTALLATION INSTRUCTIONS

RADIO SPEAKER COVERS (REAR)
PART NO. 2-487

FOR HONDA GL1500/6
GOLD WING MODELS

ITEMS REQUIRED: #2 MEDIUM PHILLIPS SCREWDRIVER

INSTALLATION:

1. REMOVE THE FOLLOWING ITEMS:
 - A. USING A #2 MEDIUM PHILLIPS SCREWDRIVER, REMOVE THE EIGHT MOUNTING SCREWS (1A) AND BOTH LEFT AND RIGHT ARM REST COVER ASSEMBLIES (1B). NOTE: OPEN THE L/R POCKET COVER DOORS (1C) FOR EASY ACCESS TO THE FRONT INBOARD SCREWS.
 - B. DISCONNECT THE REAR SPEAKER WIRING HARNESS (1D) (IF APPLICABLE) FROM THE RADIO SPEAKERS. NOTE WIRE LOCATIONS.
 - C. USING A #2 MEDIUM PHILLIPS SCREWDRIVER, REMOVE THE EIGHT MOUNTING SCREWS (2A) FROM L/R ARMREST SPEAKER COVERS (2B).
2. USING A #2 MEDIUM PHILLIPS SCREWDRIVER; INSTALL THE CHROME SPEAKER COVERS (2B) USING THE OEM SCREWS (2A) AND WASHERS PROVIDED. USE THE ADDITIONAL FOUR WASHERS PROVIDED TO ACT AS SPACERS ON THE REAR POSTS TO PREVENT THE OEM SCREWS FROM POKING THROUGH THE COVER. **CAUTION:** FAILURE TO DO SO MAY CAUSE THE CHROME PLATING TO CRACK WHEN SCREWS ARE TIGHTENED.
3. REINSTALL ALL REMOVED ITEMS BY REVERSING STEPS 1A AND 1B.

