

BIG BIKE PARTS®

INSTALLATION INSTRUCTIONS

HANDLEBAR RISER SHIMS
PART NO. 52-698

FOR HONDA
GL1800 GOLD WING

TOOLS REQUIRED: 5MM ALLEN WRENCH
14MM SOCKET
PHILLIPS SCREWDRIVER

1. REMOVE THE FRONT SPEAKER COVERS.
2. USING 5MM ALLEN WRENCH, REMOVE THE SCREW BEHIND SPEAKER COVER ON EACH SIDE. REMOVE THE BLACK PUSH RIVET ON EACH SIDE.
3. PULL THE SHELTER OFF AND UNPLUG THE PLUG UNDER THE TRIP RESET BUTTON.
4. REMOVE THE TWO PHILLIPS HEAD SCREWS THAT HOLD THE COVER OVER THE HANDLEBARS. (THESE SCREWS WILL NOT BE REUSED)
5. USING 14MM SOCKET, REMOVE THE TWO BOLTS THAT ARE HOLDING THE HANDLEBARS ON. DO ONE SIDE AT A TIME.
6. POSITION THE HANDLEBAR RISER SHIMS IN PLACE WITH THE NARROW END TOWARD THE FRONT OF THE BIKE. REINSTALL THE HANDLEBAR OVER THE RISER.
7. REINSTALL THE BLACK COVER OVER HANDLEBARS USING THE SPACERS AND LONGER SCREWS PROVIDED.
8. REINSTALL ALL REMOVED PARTS. TURN THE HANDLEBARS ALL THE WAY TO THE LEFT AND ALL THE WAY TO THE RIGHT TO MAKE SURE NOTHING IS HITTING.

Rely on premium motorcycle handlebars and controls by Big Bike Parts if you're looking for quality and efficiency.