


5203-00/5203-10 KICKSTAND INSTALLATION 2006-2009 YZ 250F/450F AND 2007-2009 WRF 250/450

5203-PK CONTENTS:



5203-PK Parts Kit



5203-00 Kickstand Installed

- A. 5905-04 Kickstand Spring
- B. 5903-00 Hanger Tab

YAMAHA INSTALLATION:

● YAMAHA YZ 250F/450F 2006-2009

1. Remove stock foot-peg, foot-peg hardware, & foot-peg hanger from frame.
2. Install provided Trail Tech foot-peg bracket, using the OEM fasteners.
Note: Use thread locking compound and manufacturers torque specification during installation.
3. Re install foot peg & foot-peg hardware following manufacturers recommended installation procedure.
4. Remove the stock side panel fastener and insert through the provided spring hanger tab (Fig. 1)

Continued on other side >>

5. Re-install the side panel fastener, and tighten down hand tight to start.

Note: Do not tighten down to manufacturers torque specification until spring is hung. Failure to do so may cause your spring to bind or break during use!



6. Hook spring into spring hanger mounting tab shown in (Fig. 2)
7. Using safety glasses & a spring puller stretch the spring and latch it onto the stand arm mounting point (Fig. 2)
8. Tighten sub-frame fastener to manufacturers torque specification.

IMPORTANT: WEAR EYE PROTECTION WHEN HANGING SPRINGS!

Note: After every ride it is important to check your kickstand thoroughly for the following:
• Loose or damaged bolts • Bent or damaged kickstand leg or bracket • Damaged spring
Damaged or broken parts can result in serious injury! If any part of your stand has become damaged do not ride the machine! Contact a factory trained technician or Trail Tech directly for service or repairs.

5204-00/5204-10 KICKSTAND INSTALLATION 2010-2015 YZ 250F/450F AND 2016 YZ 250F

5204-PK CONTENTS:



5204-00 Kickstand Installed

YAMAHA INSTALLATION:

● YAMAHA YZ 250F/450F 2010-2015 YZ 250F 2016

1. Remove stock foot-peg, foot-peg hardware, & foot-peg hanger from frame.
2. Install provided Trail Tech foot-peg bracket, using the OEM fasteners.
Note: Use thread locking compound and manufacturers torque specification during installation.
3. Re install foot peg & foot-peg hardware following manufacturers recommended installation procedure.
4. Remove the stock side panel fastener and insert through the provided spring hanger tab (Fig. 1)

5. Re-install the side panel fastener, and tighten down hand tight to start.
Note: Do not tighten down to manufacturers torque specification until spring is hung. Failure to do so may cause your spring to bind or break during use!
6. Hook spring into spring hanger mounting tab shown in (Fig. 2)
7. Using safety glasses & a spring puller stretch the spring and latch it onto the stand arm mounting point (Fig. 2)
8. Tighten sub-frame fastener to manufacturers torque specification.

Continued on other side >>

IMPORTANT: WEAR EYE PROTECTION WHEN HANGING SPRINGS!

Note: After every ride it is important to check your kickstand thoroughly for the following:
 • Loose or damaged bolts • Bent or damaged kickstand leg or bracket • Damaged spring
 Damaged or broken parts can result in serious injury! If any part of your stand has become damaged do not ride the machine! Contact a factory trained technician or Trail Tech directly for service or repairs.