
ROTORS

Produced by a premier disc brake manufacturer for Twin Power, our direct bolt-on rotors are specially ground to help prevent warping. They are laser cut 11.5 in. rotors and includes aluminum adaptor ring to fit 84–99 H–D® models with 2 in. center hole. CNC billet-machined carriers on floating rotors.









Solid Mesh

Floating Mesh Black

Floating Hole Silver

			Tech	Floating Mesh	Floating Mesh	Floating Hole	Floating Hole	Solid	Solid	
HARLEY-DAVIDSON	Year O.E.M.	Size	Notes	Black	Silver	Black	Silver	Mesh	Hole	
Dyna	06-13	11.8 in.		666820	666822	666821	666823	666824	666825	
FXST	84-15	11.5 in.	Front	666832	666834	666833	666835	666836	666837	
FLST	86-15	11.5 in.	Front	666832	666834	666833	666835	666836	666837	
FXD	94-15	11.5 in.	Front	666832	666834	666833	666835	666836	666837	
XL	84-13	11.5 in.	Front	666832	666834	666833	666835	666836	666837	
<u>FLH</u>	08-15	11.8 in.	Rear	666820	666822	666827	666835	666836	666837	
H-D Models										
(exc. 08–15 Touring)	84-15	11.5 in.	Rear	666838	666840	6668392	666841	666842	666843	
FL	78-84 41813-79	10 in.	Front or	Rear					6668441	

¹² in, center, 3/8 in, ciunter bore holes