

2018 SUZUKI GSXR-250 S1R Slip-On Part # 005-50504-S1B

Image 1



3. Slide the TBR slip tube onto the header with the included clamp. (Reference image 3)

Slide the muffler onto the slip tube and attach it using the supplied springs as shown. (Reference image 4) 4.







5. Using the supplied hardware install the muffler clamp as shown. Use the included spacer between the clamp and passenger peg bracket. (Reference image 5)



- Once you ensure the exhaust is fitted properly, begin to tighten all hardware. 6.
- 7. Before you run the bike, clean off all fingerprints and dirt, as any oily residue will etch the metal and become somewhat permanent when the system gets hot. Run the bike and enjoy. It is normal for some white smoke to appear the first time you start the bike. This is packing/manufacturing oil from inside the pipe burning off. Check for gaps or leaks. If you find a leak, a little high temperature silicon sealant should fix it. After 50 to 100 miles, recheck all fasteners for tightness.

IMPORTANT - PLEASE READ CAREFULLY: We recommend that this performance part be installed by a qualified motorcycle technician. If you have any doubts as to your ability to install this performance part, please consult with your local motorcycle dealer. Read all instructions first before starting installation. Make sure the motorcycle and exhaust system are completely cool before starting the installation. Also, make sure the bike is secure on a center stand or ideally a service lift during installation. Be sure to save all stock components for possible use later.

WARRANTY: Two Brothers Racing products are intended for closed course competition purposes only, and therefore are sold "as is" without warranty. Two Brothers Racing specifically disclaims any warranties of merchantability or fitness for a particular purpose and disclaims all responsibility for consequential and incidental damages or any other losses arising from the use of these products or parts.

BILL OF MATERIALS

1	S1R Muffler	
1	8mm Flange Nut	005-FN8
2	45mm Springs	005-S45
1	18mm Spacer	005-S-18
1	8x60mm Bolt	005-SH860
1	S1R Vertical Clamp	005-2C-S1
1	S1R Vertical Clamp Liner	005-2C-S1-A
1	59mm Barrel Clamp	005-27-59MSH
1	Spring Puller	005-SP

INSTALLATION INSTRUCTIONS

- Make sure the motorcycle is completely cool before installation, and make sure it is secure on a stand. 1.
- 2. Loosen the OEM muffler bracket and clamp. (Reference image 1 & 2)



BILL OF MATERIALS		
1	S1R Muffler	
1	8mm Flange Nut	005-FN8
2	45mm Springs	005-S45
1	18mm Spacer	005-S-18
1	8x60mm Bolt	005-SH860
1	S1R Vertical Clamp	005-2C-S1
1	S1R Vertical Clamp Liner	005-2C-S1-A
1	59mm Barrel Clamp	005-27-59MSH
1	Spring Puller	005-SP

Care & Cleaning

Keep system free of dirt and moisture. Store in a cool, dry place. Make sure vehicle is completely cool before maintenance.

Stainless Header System: Polished stainless steel pipes will turn a light golden hue after a few heat cycles, this is a normal characteristic of high quality stainless steel. Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth.

Titanium Header System: Polished titanium pipes will experience color shift ranging from deep blue/purple through amber after a few heat cycles. This is a normal characteristic of high quality titanium. Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth.

Polished Aluminum Canisters: Use an aluminum or mag wheel polish to restore the bright finish to factory spec.

Brushed Aluminum Canisters: Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth.

Carbon Fiber Canisters: Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth. Always make sure the fiberglass packing inside is in good condition and not burned out, as exhaust heat inside an empty canister will deteriorate the carbon fiber sleeve. TBR sells repack kits (Road - #005-10038, Offroad - #005-10038MX) that include everything you need to easily do it yourself.

Titanium Mufflers: For cleaning use a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth. Always make sure the fiberglass packing inside is in good condition and not burned out, as exhaust heat inside an empty canister will deteriorate the carbon fiber sleeve.

TBR sells repack kits (Road - #005-10038, Offroad - #005-10038MX) that include everything you need to easily do it yourself.

Repack all road canisters at the first signs of packing material deterioration. Part #005-10038 Repack all offroad canisters after every 10 hours of use. Part #005-10038MX

NEVER dyno test your bike with carbon fiber or titanium canisters installed - the intense heat and lack of cooling air can quickly burn through the canister material. Two Brothers Racing does not provide a warranty for burned canisters.

