

## VALVOLINE<sup>™</sup> 4-STROKE SYNTHETIC MOTORCYCLEOIL

Valvoline <u>4-Stroke Synthetic Motorcycle Oils are designed specifically for motorcycles</u>. Motorcycles place special demands on engine oil that automotive oils are not designed to handle. The wet clutch system, high RPMs and temperatures, and metals found in motorcycles require special properties for proper performance and protection. Valvoline Synthetic MotorcycleOils use the highest quality synthetic base oils and advanced additives to bring out the best in your machine.

## Valvoline 4-Stroke Synthetic Motorcycle Oil advantages:

- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Maximizes power and acceleration
- Excellent wear and corrosion protection
- Added protection against harmful deposits
- Excellent Shear Stability
- Excellent Film Strength
- For use in 4-Stroke Motorcycles, including Cruisers and Off-Road Motorcycles

Approvals and Licenses:	SAE 10W-40	SAE 20W-50	
Meets or Exceeds API SF/SG/SJ	YES	YES	
Meets or Exceeds JASO MA2	YES	YES	

Typical Properties:	SAE 10W-40	SAE 20W-50	
Vis @ 100°C (cSt)	14.1	20.5	
Vis @ 40°C (cSt)	95.4	162	
Viscosity Index	152	147	
Spec Gravity @ 60°F	0.858	0.8606	
Density (lbs/gal)	7.16	7.34	
Total Base No.	8	8	
Flash COC (°C)	225	230	
Pour Point (°C) max	-39	-36	
CCS cP (°C)	6200(-25 <sup>0</sup> C)	5200(-15 <sup>0</sup> C)	
MRV TP-1 cP (°C)	38000(-30 <sup>0</sup> C)	28000(-20 <sup>0</sup> C)	
Noack % off @ 250°C	<15.0	<15.0	
Sulfated Ash, wt.%	0.80	0.80	
Zinc/Phosphorus, wt.%	0.112/0.100	0.112/0.100	
Calcium/Sodium, wt.%	0.188/0.052	0.188/0.052	

This information only applies to products manufactured in the following location(s):

Effective Date:	Replaces:	Author's Initials:	Pages	Code
10-8-10		DJD		Rev 000