## **SQUARE LED**

## EF LED WORK UTILITY LIGHTS / POWER OUTPUT: 15 - 27 WATTS

- Dimensions: 4.3" x 5.0" (5-LED configuration)
- Dimensions: 4.6" x 5.3" (9-LED configuration)
- 3W Epistar LED Chips
- Dust and moisture resistant lens
- Raw Lumens: 800 1,450
- · Pivoting base mount bracket
- · Includes mounting hardware and pigtail connector
- · Limited lifetime warranty
- · Available in Flood or Spot beam





PART NO.	POWER OUTPUT	BEAM Type	LEDS	FACE SIZE	RAW Lumens	BEAM Distance	OPERATING Voltage
09-12210A	15	Spot	5 x 3W Epistar	4.3"	800	265	9V-30V
09-12210	15	Flood	5 x 3W Epistar	4.3"	800	120	9V-30V
09-12211A	27	Spot	9 x 3W Epistar	4.6"	1450	325	9V-30V
09-12211B	27	Flood	9 x 3W Epistar	4.6"	1450	175	9V-30V

— BEAM PATTERNS —

FLOOD

 MODEL
 A
 B
 C
 D

 09-12210
 4.3 in.
 1.6 in.
 5.0 in.
 5.4 in.

 MODEL
 A
 B
 C
 D

 MODEL
 A
 B
 C
 D

 09-12211
 4.6 in.
 2.0 in.
 5.3 in.
 5.7 in.





